

# Epitax



Pull-out downlight that, having **no flange** and featuring **recessed optics**, seamlessly blends in with the architecture emphasizing volumes. Epitax can be either mounted in a recessed position flush with the false ceiling or in a semi-recessed position by simply rotating the flange.

**Trimless**

It can be installed semi-recessed or in a recessed position flush with the surface.

**Passive heat dissipation**

Die cast aluminium heat sink

**Graceful aesthetics**


Optical compartment with embossed or "warm & chic" golden finish

**Polycarbonate casing (8 W and 15 W version)**

No overheating of the installation surface.




**Epitax** | Downlight | powerLED 2 W 630 mA



type		colour			optic	
White	CRI 80 <b>97102</b>	2700 K	195 lm	<b>M</b>	8°	<b>08</b>
Black	CRI 80 <b>97103</b>	3000 K	208 lm	<b>W</b>	15°	<b>15</b>
Gold	CRI 80 <b>97104</b>	4000 K	222 lm	<b>N</b>	30°	<b>30</b>
					45°	<b>45</b>

<b>89147</b>	<b>99115</b>	<b>99114</b>
ON/OFF 1 - 2 art.	1-10V 1 - 10 art.	DALI 1 - 10 art.


**Epitax** | Downlight | powerLED 6 W 500 mA



type		colour			optic	
White	CRI 80 <b>91384</b>	2700 K	660 lm	<b>M</b>	15°	<b>15</b>
Black	CRI 80 <b>91385</b>	3000 K	712 lm	<b>W</b>	45°	<b>45</b>
Gold	CRI 80 <b>91389</b>	4000 K	764 lm	<b>N</b>		

<b>99128</b>	<b>99115</b>	<b>99114</b>
ON/OFF 1 art.	1-10V 1 - 3 art.	DALI 1 - 3 art.


**Epitax** | Downlight | powerLED 8 W 630 mA



type		colour			optic	
White	CRI 80 <b>97105</b>	2700 K	639 lm	<b>M</b>	15°	<b>15</b>
Black	CRI 80 <b>97106</b>	3000 K	674 lm	<b>W</b>	30°	<b>30</b>
Gold	CRI 80 <b>97107</b>	4000 K	745 lm	<b>N</b>	60°	<b>60</b>

<b>99129</b>	<b>99115</b>	<b>99114</b>
ON/OFF 1 art.	1-10V 1 - 2 art.	DALI 1 - 2 art.

**Epitax** | Downlight | powerLED 15 W 400 mA



type		colour			optic	
White	CRI 95 <b>97111</b>	2700 K	1070 lm	<b>M</b>	15°	<b>15</b>
Black	CRI 95 <b>97112</b>	3000 K	1160 lm	<b>W</b>	30°	<b>30</b>
Gold	CRI 95 <b>97113</b>				60°	<b>60</b>

White	CRI 80 <b>97108</b>	2700 K	1446 lm	<b>M</b>	15°	<b>15</b>
Black	CRI 80 <b>97109</b>	3000 K	1560 lm	<b>W</b>	30°	<b>30</b>
Gold	CRI 80 <b>97110</b>	4000 K	1670 lm	<b>N</b>	60°	<b>60</b>


<b>99113</b>	<b>99116</b>	<b>99131</b>
ON/OFF 1 art.	1-10V 1 art.	DALI 1 art.

**Epitax 2 W | Frameless outer-casing**



type

Anod. Al. **98501**



**Epitax 2 W | Outer-casing**




type

White **98527**

Black **98528**

Gold **98529**




**Epitax 6 W | Frameless outer-casing**



type

Anod. Al. **98502**



**Epitax 6 W | Outer-casing**




type


White **98530**

Black **98531**

Gold **98532**




**Epitax 8 W | Frameless outer-casing**



type

Anod. Al. **98499**



**Epitax 8 W | Outer-casing**




type

White **98533**

Black **98534**

Gold **98535**




**Epitax 15 W | Frameless outer-casing**



type

Anod. Al. **98500**



**Epitax 15 W | Outer-casing**



type

White **98536**

Black **98537**

Gold **98538**









