

# Arcada



Perfect for arches, lintels or even jambs, statues and reliefs. An indirect lighting with a homogeneous intensity involving the entire structure right from its base can be obtained through a photometric solid that **precisely follows the arch intrados**, avoiding unaesthetic hot spots and glare and **minimizing light pollution**.

**Passive heat dissipation**

Die cast aluminium casing

**Light management**

Arch-shaped emission with a very narrow shape of the photometric solid coming out of the diffuser shorter side


**Specialised functionality**

Ideal lighting for windows and depressed arches with no glare or light pollution

5° ↗




**Arcada** | Arc light | 190-250 V | powerLED 4 W 350 mA





type		colour			optic	
White	CRI 80 <b>95454</b>	2700 K	484 lm	<b>M</b>	180°	<b>18</b>
Black	CRI 80 <b>95612</b>	3000 K	520 lm	<b>W</b>		
Grey	CRI 80 <b>95619</b>	4000 K	552 lm	<b>N</b>		


**Arcada** | Arc light | powerLED 8 W 630 mA



type		colour			optic	
White	CRI 80 <b>95458</b>	2700 K	780 lm	<b>M</b>	180°	<b>18</b>
Black	CRI 80 <b>95616</b>	3000 K	832 lm	<b>W</b>		
Grey	CRI 80 <b>95623</b>	4000 K	888 lm	<b>N</b>		

	
<b>99179</b>	<b>99186</b>
ON/OFF 1 art.	ON/OFF 2 - 3 art.

**Arcada** | Arc light | powerLED 7.5 W 220 mA



type		colour			optic	
White	<b>95749</b>	RGB		<b>Z</b>	180°	<b>18</b>
Black	<b>95750</b>					
Grey	<b>95751</b>					

		
<b>99140</b>	<b>99204</b>	<b>99200</b>
N/O & IR	DMX	DMX

