

Guardian



The ultimate outdoor downlight: powerful and with four optics available, it can be used also at remarkable heights. It is highly resistant and requires no maintenance, thus becoming the ideal partner for outdoor lighting projects.

Passive heat dissipation

Black casing and anodised aluminium flange available in three finishes

Light management


Four optics available for maximum design flexibility

Reliable outdoor installations

Maximum resistance against mechanical impacts and a higher cable protection against water and humidity thanks to the Aqua-Stop system



Guardian | Downlight | 190-250 V | powerLED 8 W 630 mA




type		colour			optic	
White	CRI 80 96089	2700 K	639 lm	M	15°	15
Black	CRI 80 96090	3000 K	674 lm	W	30°	30
Grey	CRI 80 96091	4000 K	745 lm	N	60°	60
					Asym.	07



98396
Outer casing

Guardian | Downlight | 180-300 V | powerLED 13 W 350 mA




type		colour			optic	
White	CRI 80 96092	2700 K	1298 lm	M	15°	15
Black	CRI 80 96093	3000 K	1400 lm	W	30°	30
Grey	CRI 80 96094	4000 K	1497 lm	N	60°	60



98397
Outer casing

Guardian | Downlight | 180-300 V | arrayLED 25 W 720 mA



type		colour			optic	
White	CRI 80 96095	2700 K	3101 lm	M	15°	15
Black	CRI 80 96096	3000 K	3321 lm	W	30°	30
Grey	CRI 80 96097	4000 K	3568 lm	N	60°	60
					Asym.	07




98397
Outer casing

Guardian | Outer-casing



type	Ø mm	h. mm	suitable for	
PVC	160	163	Guardian 8 W	98396

Guardian | Outer-casing



type	Ø mm	h. mm	suitable for	
PVC	300	186	Guardian 13 W - 25 W	98397

