

TYCO 20 LED

design by SILVIA PAOLA PENNACCHIO



- GR-94 / Metallic grey / Textured
- BK-81 / Black / Textured

LED floodlight for indoor and outdoor lighting, comprising:

- Die-cast aluminum housing chemically pre-treated and painted with polyester powder coating
- Flat tempered glass diffuser
- Technopolymer reflector with high efficiency aluminium protective surface treatment
- Anti-ageing silicone gasket
- Waterproof cable gland M16x1.5 for cables Ø 5- Ø 10 mm
- Power supply units housed inside the box
- Switch splitter that automatically disconnects the power supply when the cable cover is opened (TYCO 20)
- High power LEDs with next generation high intensity light beam
- Aluminium heat sink
- Stainless steel external screws
- Luminaire designed for optical compartment adjustment with dedicated screws on the stem
- On demand, the luminaire can be supplied with separate louvre and power supply unit (version Tyco 21 LED + Box, two product codes to be ordered at the same time)




TYCO 20 LED
C/I



TYCO 20 LED
C/M 23



TYCO 20 LED
C/M 40



TYCO 20 LED C/I

IK08 6J xx5

LAMPHOLDER	WATTAGE	CLASS	☀️	CRI	KELVIN	COS Φ ≥ 0,9	OPTIC	OPTIC BEAM	LIGHTSOURCE LUMEN OUTPUT	LUMINAIRE LUMEN OUTPUT	L	B	LIFETIME	COLOUR/ RAL	PART NUMBER
Power LED 220-240 V 50/60 Hz															
LED	33 W	II		70	5000	•	C/I	15°	4962 lm	2468 lm	80	10	130000 h	●	06122794
LED	33 W	II		80	4000	•	C/I	15°	4238 lm	2174 lm	80	10	130000 h	●	06122594
LED	33 W	II		80	3000	•	C/I	15°	4047 lm	2146 lm	80	10	130000 h	●	06122394
LED	33 W	II		70	5000	•	C/I	15°	4962 lm	2468 lm	80	10	130000 h	●	06122681
LED	33 W	II		80	4000	•	C/I	15°	4238 lm	2174 lm	80	10	130000 h	●	06122481
LED	33 W	II		80	3000	•	C/I	15°	4047 lm	2146 lm	80	10	130000 h	●	06122281



TYCO 20 LED C/M

IK08 6J xx5

LAMPHOLDER	WATTAGE	CLASS	☀️	CRI	KELVIN	COS Φ ≥ 0,9	OPTIC	OPTIC BEAM	LIGHTSOURCE LUMEN OUTPUT	LUMINAIRE LUMEN OUTPUT	L	B	LIFETIME	COLOUR/ RAL	PART NUMBER
Power LED 220-240 V 50/60 Hz															
LED	33 W	II		70	5000	•	C/M	23°	4962 lm	2205 lm	80	10	130000 h	●	06123394
LED	33 W	II		70	5000	•	C/M	40°	4962 lm	2168 lm	80	10	130000 h	●	06123994
LED	33 W	II		80	4000	•	C/M	23°	4238 lm	1945 lm	80	10	130000 h	●	06123194
LED	33 W	II		80	4000	•	C/M	40°	4238 lm	1893 lm	80	10	130000 h	●	06123794
LED	33 W	II		80	3000	•	C/M	23°	4047 lm	1927 lm	80	10	130000 h	●	06122994
LED	33 W	II		80	3000	•	C/M	40°	4047 lm	1878 lm	80	10	130000 h	●	06123594
LED	33 W	II		70	5000	•	C/M	23°	4962 lm	2205 lm	80	10	130000 h	●	06123281
LED	33 W	II		70	5000	•	C/M	40°	4962 lm	2168 lm	80	10	130000 h	●	06123881
LED	33 W	II		80	4000	•	C/M	23°	4238 lm	1945 lm	80	10	130000 h	●	06123081
LED	33 W	II		80	4000	•	C/M	40°	4238 lm	1893 lm	80	10	130000 h	●	06123681
LED	33 W	II		80	3000	•	C/M	23°	4047 lm	1927 lm	80	10	130000 h	●	06122881
LED	33 W	II		80	3000	•	C/M	40°	4047 lm	1878 lm	80	10	130000 h	●	06123481




OPTIONAL ACCESSORIES


DESCRIPTION	COLOR	PART NUMBER
TYCO 20 LED		
Frosted glass.		14065220
External aluminium cowl finished polyester aluminium grey.	●	14064994
External aluminium cowl finished polyester painted matt black.	●	14065081
Pole mounting clamp finished aluminium grey suitable for TYCO 20 or Box TYCO 21 only.	●	14065894
Pole mounting clamp finished black suitable for TYCO 20 or Box TYCO 21 only.	●	14065981
Galvanised steel ground mounting spike, for TYCO 20 or Box TYCO 21.		14065602
Ground/ceiling angle bracket. (TYCO 20)		14065502
M16x1.5 anti-tearing cable gland for through-wiring.		14066020



14065220



14065094




14065894



14065602



14065502



14066020

max 3,2 kg

0,060 m²

