

Vos

F.O.L.™



Fire Rating®



Tilting



The families of Vos downlights are characterized by an **optical unit consisting of a reflector with F.O.L.™ filtering system**. The fixed and tilting versions, with the exception of the asymmetric version, feature a **pinhole controlled-reflectance optical compartment** with a recessed light source fitted with anti-glare screen.


Passive heat dissipation
Die cast aluminium heat sink

Light management
Black-coated aluminium casing and optical compartment

Minimalist sturdiness
Thin yet resistant steel flange with embossed finish




Vos_R | Downlight | powerLED 8 W 630 mA



type		colour			optic	
White	CRI 80 95510	2700 K	639 lm	M	15°	15
Black	CRI 80 95511	3000 K	674 lm	W	30°	30
		4000 K	745 lm	N	60°	60

99129	99115	99114
ON/OFF 1 art.	1-10V 1 - 2 art.	DALI 1 - 2 art.

Vos_R | Downlight | powerLED 15 W 400 mA




type		colour			optic	
White	CRI 95 95524	2700 K	1070 lm	M	15°	15
Black	CRI 95 95525	3000 K	1160 lm	W	30°	30
					45°	45

White	CRI 80 95512	2700 K	1446 lm	M	15°	15
Black	CRI 80 95513	3000 K	1560 lm	W	30°	30
		4000 K	1670 lm	N	45°	45

99113	99116	99131
ON/OFF 1 art.	1-10V 1 art.	DALI 1 art.

Vos_R | Downlight | arrayLED 25 W 720 mA




type		colour			optic	
White	CRI 95 95548	2700 K	2347 lm	M	15°	15
Black	CRI 95 95549	3000 K	2511 lm	W	30°	30
		4000 K	2695 lm	N	45°	45

White	CRI 80 95536	2700 K	3101 lm	M	15°	15
Black	CRI 80 95537	3000 K	3321 lm	W	30°	30
		4000 K	3568 lm	N	45°	45

99112	99188	99330
ON/OFF 1 art.	1-10V, DALI 1 art.	DALI 1 art.

Vos_RJ | Downlight | powerLED 8 W 630 mA



64

type

White	CRI 80	95824
Black	CRI 80	95825

colour

2700 K	639 lm	M
3000 K	674 lm	W
4000 K	745 lm	N

optic

15°	15
30°	30
60°	60



99129

ON/OFF
1 art.


99115

1-10V
1 - 2 art.

99114

DALI
1 - 2 art.

Vos_RJ | Downlight | powerLED 15 W 400 mA



95

type

White	CRI 80	95865
Black	CRI 80	95866

colour

2700 K	1446 lm	M
3000 K	1560 lm	W
4000 K	1670 lm	N

optic

15°	15
30°	30
45°	45



99113

ON/OFF
1 art.


99116

1-10V
1 art.

99131

DALI
1 art.

Vos_RJ | Downlight | arrayLED 25 W 720 mA



121

type

White	CRI 95	96285
Black	CRI 95	96286

colour

2700 K	2347 lm	M
3000 K	2511 lm	W
4000 K	2695 lm	N

optic

15°	15
30°	30

White	CRI 80	95958
Black	CRI 80	95959

2700 K	3101 lm	M
3000 K	3321 lm	W
4000 K	3568 lm	N

15°	15
30°	30



99112

ON/OFF
1 art.


99188

1-10V, DALI
1 art.

99330

DALI
1 art.


Vos_Q | Downlight | powerLED 8 W 630 mA



type		colour			optic	
White	CRI 80	95560	2700 K	639 lm	M	15° 15
Black	CRI 80	95561	3000 K	674 lm	W	30° 30
			4000 K	745 lm	N	60° 60

99129	99115	99114
ON/OFF 1 art.	1-10V 1 - 2 art.	DALI 1 - 2 art.

Vos_Q | Downlight | powerLED 15 W 400 mA




type		colour			optic	
White	CRI 95	95574	2700 K	1070 lm	M	15° 15
Black	CRI 95	95575	3000 K	1160 lm	W	30° 30
						45° 45

White	CRI 80	95562	2700 K	1446 lm	M	15° 15
Black	CRI 80	95563	3000 K	1560 lm	W	30° 30
			4000 K	1670 lm	N	45° 45

99113	99116	99131
ON/OFF 1 art.	1-10V 1 art.	DALI 1 art.

Vos_Q | Downlight | arrayLED 25 W 720 mA




type		colour			optic	
White	CRI 95	95598	2700 K	2347 lm	M	15° 15
Black	CRI 95	95599	3000 K	2511 lm	W	30° 30
			4000 K	2695 lm	N	45° 45

White	CRI 80	95586	2700 K	3101 lm	M	15° 15
Black	CRI 80	95587	3000 K	3321 lm	W	30° 30
			4000 K	3568 lm	N	45° 45

99112	99188	99330
ON/OFF 1 art.	1-10V, DALI 1 art.	DALI 1 art.

Vos_QY | Downlight | arrayLED 25 W 720 mA



type

White	CRI 80	95857
Black	CRI 80	95858

colour

2700 K	3101 lm	M
3000 K	3321 lm	W
4000 K	3568 lm	N

optic

Asym.	07
-------	-----------


**99112**ON/OFF
1 art.**99188**1-10V, DALI
1 art.**99330**DALI
1 art.

"Messe" - Düsseldorf (Germany)

Installed in the ceiling in the reception area of the Messe Düsseldorf GmbH, Vos_Q ensures a pure, well-defined asymmetric light beam with a controlled wall projection. The light illuminates the entrance walls in an effective yet discreet way.




Vos_QJ | Downlight | powerLED 8 W 630 mA



type		colour			optic	
White	CRI 80 95826	2700 K	639 lm	M	15°	15
Black	CRI 80 95827	3000 K	674 lm	W	30°	30
		4000 K	745 lm	N	60°	60

99129 ON/OFF 1 art.	99115 1-10V 1 - 2 art.	99114 DALI 1 - 2 art.


Vos_QJ | Downlight | powerLED 15 W 400 mA



type		colour			optic	
White	CRI 80 95956	2700 K	1446 lm	M	15°	15
Black	CRI 80 95957	3000 K	1560 lm	W	30°	30
		4000 K	1670 lm	N	45°	45

99113 ON/OFF 1 art.	99116 1-10V 1 art.	99131 DALI 1 art.

Vos_QJ | Downlight | arrayLED 25 W 720 mA



type		colour			optic	
White	CRI 95 96287	2700 K	2347 lm	M	15°	15
Black	CRI 95 96288	3000 K	2511 lm	W	30°	30
		4000 K	2695 lm	N		
White	CRI 80 95960	2700 K	3101 lm	M	15°	15
Black	CRI 80 95961	3000 K	3321 lm	W	30°	30
		4000 K	3568 lm	N		

99112 ON/OFF 1 art.	99188 1-10V, DALI 1 art.	99330 DALI 1 art.

