


ISTHAR/LED

design by SILVIA PAOLA PENNACCHIO



● GR-11 / Anodised grey / Matt



Wall and ceiling mounted LED luminaire for indoor and outdoor applications, comprising:


- Extruded anodised aluminium housing
- Diffuser in flat glass, internally frosted
- End caps in painted die-cast aluminium
- Extra pure polished aluminium reflectors
- Anti-ageing silicone gasket
- Cable gland M18x1.5 for cables Ø 8- Ø 10.5 mm
- Light beam obtained by the combination of multiple LED modules
- Aluminium heat sink
- Fully integrated stainless steel aluminium spring clips
- Stainless steel external screws
- Technopolymer closing hinges for glass
- Die-cast painted aluminium ceiling or wall mount brackets
- The brackets allow ceiling lamp adjustments by $\pm 12^\circ$
- Supplied with anti-vacuum valve



ISTHAR/LED S/M

IK07 3J xx5

LAMPHOLDER	WATTAGE	CLASS	CRI	KELVIN	COS ϕ $\geq 0,9$	OPTIC	OPTIC BEAM	LIGHTSOURCE LUMEN OUTPUT	LUMINAIRE LUMEN OUTPUT	L	B	LIFETIME	COLOUR/ RAL	PART NUMBER
LED	67 W	II	80	5000	•	S/M	-	7590 lm	4785 lm	80	10	40000 h	●	06089211
LED	67 W	II	80	4000	•	S/M	-	7480 lm	4233 lm	80	10	40000 h	●	06087511
LED	53 W	II	80	5000	•	S/M	-	6072 lm	3820 lm	80	10	40000 h	●	06088811
LED	53 W	II	80	4000	•	S/M	-	5984 lm	3380 lm	80	10	40000 h	●	06087111
LED	40 W	II	80	5000	•	S/M	-	4554 lm	2660 lm	80	10	40000 h	●	06088411
LED	40 W	II	80	4000	•	S/M	-	4488 lm	2535 lm	80	10	40000 h	●	06086711



1000 mm / 40 W
1300 mm / 53 W
1600 mm / 67 W

ISTHAR/LED S/W

IK07 3J xx5

LAMPHOLDER	WATTAGE	CLASS	CRI	KELVIN	COS ϕ $\geq 0,9$	OPTIC	OPTIC BEAM	LIGHTSOURCE LUMEN OUTPUT	LUMINAIRE LUMEN OUTPUT	L	B	LIFETIME	COLOUR/ RAL	PART NUMBER
LED	67 W	II	80	5000	•	S/W	-	7590 lm	4568 lm	80	10	40000 h	●	06089011
LED	67 W	II	80	4000	•	S/W	-	7480 lm	4042 lm	80	10	40000 h	●	06087411
LED	53 W	II	80	5000	•	S/W	-	6072 lm	3626 lm	80	10	40000 h	●	06088611
LED	53 W	II	80	4000	•	S/W	-	5984 lm	3208 lm	80	10	40000 h	●	06087011
LED	40 W	II	80	5000	•	S/W	-	4554 lm	2236 lm	80	10	40000 h	●	06088211
LED	40 W	II	80	4000	•	S/W	-	4488 lm	2354 lm	80	10	40000 h	●	06086611

ISTHAR/LED S/EW

IK07 3J xx5

LAMPHOLDER	WATTAGE	CLASS	CRI	KELVIN	COS ϕ $\geq 0,9$	OPTIC	OPTIC BEAM	LIGHTSOURCE LUMEN OUTPUT	LUMINAIRE LUMEN OUTPUT	L	B	LIFETIME	COLOUR/ RAL	PART NUMBER
LED	67 W	II	80	5000	•	S/EW	-	7590 lm	4194 lm	80	10	40000 h	●	06089111
LED	67 W	II	80	4000	•	S/EW	-	7480 lm	3712 lm	80	10	40000 h	●	06087611
LED	53 W	II	80	5000	•	S/EW	-	6072 lm	3379 lm	80	10	40000 h	●	06088711
LED	53 W	II	80	4000	•	S/EW	-	5984 lm	2990 lm	80	10	40000 h	●	06087211
LED	40 W	II	80	5000	•	S/EW	-	4554 lm	2286 lm	80	10	40000 h	●	06088311
LED	40 W	II	80	4000	•	S/EW	-	4488 lm	2023 lm	80	10	40000 h	●	06086811


ISTHAR/LED A/W

IK07 3J xx5


LAMPHOLDER	WATTAGE	CLASS	CRI	KELVIN	COS ϕ $\geq 0,9$	OPTIC	OPTIC BEAM	LIGHTSOURCE LUMEN OUTPUT	LUMINAIRE LUMEN OUTPUT	L	B	LIFETIME	COLOUR/ RAL	PART NUMBER
LED	67 W	II	80	5000	•	A10/W	-	7590 lm	4055 lm	80	10	40000 h	●	06088911
LED	67 W	II	80	4000	•	A10/W	-	7480 lm	3589 lm	80	10	40000 h	●	06087711
LED	53 W	II	80	5000	•	A10/W	-	6072 lm	3373 lm	80	10	40000 h	●	06088511
LED	53 W	II	80	4000	•	A10/W	-	5984 lm	2985 lm	80	10	40000 h	●	06087311
LED	40 W	II	80	5000	•	A10/W	-	4554 lm	2730 lm	80	10	40000 h	●	06088111
LED	40 W	II	80	4000	•	A10/W	-	4488 lm	2416 lm	80	10	40000 h	●	06086911

OPTIONAL ACCESSORIES


DESCRIPTION	COLOR	PART NUMBER
ISTHAR		
Pair of stainless steel wall brackets.		14041220
Pair of sheet steel 100mm adjustable brackets finished, suitable for wall or ceiling installation.		14032294
Pair of sheet steel 300mm adjustable brackets finished, suitable for wall or ceiling installation.		14032394
Pair 2m wire suspension cables, suitable for indoor installation only.		14032420
Pair 2m wire suspension cables with ceiling roses finished, for indoor installation only.		14041320



14041220




14032294



14032394






14032420



14041320

ISTHAR n. 40 W	ISTHAR n. 53 W	ISTHAR n. 67 W
max 4 kg	max 5 kg	max 6 kg



GRILLE PROTECT



- Wire guards for surface mount fluorescent luminaires
- Stand-alone wire guard from surface fitting
- Galvanised 4mm steel wire guard
- Complete with two surface mounting brackets, allowing the grid to stay in place during lamp replacement
- Suitable for various surface mount fluorescent fittings, reduces light output between 5 %-8 %

OPTIONAL ACCESSORIES

POWER	L (mm)	CODE
1x18 W	695	14-00042
1x36 W	1295	14-00043
1x58 W	1595	14-00044
2x18 W	695	14-00045
2x36 W	1295	14-00046
2x58 W	1595	14-00047

