



# LATTE IP54 LED



L80 B10 >54 000h • SDCM 3 • LLMF 88% • CRI 83

MOC	ŹRÓDŁO	STRUMIENŃ OPRAWY	SKUTECZNOŚĆ OPRAWY	[kg]	KOLOR	KOD
POWER	LAMP	LUMINAIRE'S LUMINOUS FLUX	LUMINAIRE'S EFFICACY	[kg]	COLOUR	CODE
19 W	LED 3000 K	1870 lm	98 lm/W	1,70	□	PX1789029
19 W	LED 4000 K	1900 lm	100 lm/W	1,70	□	PX1789036
24 W	LED 3000 K	2950 lm	123 lm/W	2,00	□	PX1789001
24 W	LED 4000 K	3010 lm	125 lm/W	2,00	□	PX1789008
46 W	LED 3000 K	5680 lm	123 lm/W	2,60	□	PX1789015
46 W	LED 4000 K	5800 lm	126 lm/W	2,60	□	PX1789022


NOWOŚĆ



LATTE IP54 LED wyłączona  
LATTE IP54 LED OFF



LATTE IP54 LED włączona  
LATTE IP54 LED ON



LATTE IP54 SQUARE LED  
LATTE IP54 SQUARE LED



Łatwy montaż oraz system otwierania klosza  
Easy installation and diffuser dismantling system




Uszczelnienie oprawy  
Protection seals


## LATTE IP54 LED

**Wykonanie:** podstawa z tworzywa w kolorze białym. Klosz OPAL odporny na UV.  
**Montaż:** nastropowy, naścienny  
**Zasilanie:** 220 V - 240 V

**Materials:** base made of plastic in white colour. OPAL UV-proof diffuser.  
**Installation:** ceiling mounted, wall mounted  
**Power supply:** 220 V - 240 V



LATTE IP54 SQUARE LED



LATTE IP54 LED

WYMIARY  
DIMENSIONS

	L	W	H
	[mm]	[mm]	[mm]
19 W	330	330	85
24 W	1160	110	90
46 W	1160	160	90

