




NEXTREMA LED

WEATHER-PROOF
LED LUMINAIRES,
HIGHLY EFFICIENT



THE TOUGH WEATHER-PROOF LUMINAIRE FOR EXTREME SITUATIONS



- Especially suitable for use in extreme operating environments such as cold stores or car parks. Also for use in the food industry with polycarbonate diffuser.
- With a length of just 1 metre, the Nextrema LED achieves the same lumen output as standard 1.5 metre weather-proof luminaires.
- Optional presence sensors enable configurations according to requirements and reliable light management, with "running" light for example in car parks.



Higher output: up to 113 lm/W Intelligent control





Surface-mounted weather-proof luminaires, PMMA



Reference	TOC	...ETDD	...ET		EEC	W	≈kg
• Nextrema 4000-840...+HFS TWW	60 968...	-	...40	4500 lm	A++/A+/A	40	1.9
Nextrema 4000-840...+HFS+LV TWW	60 969...	-	...40	4500 lm	A++/A+/A	40	1.9
Nextrema 4000-840...+LV TWW	60 967...	...51	...40	4500 lm	A++/A+/A	40	1.9
Nextrema 4000-840...TWW	60 966...	...51	...40	4500 lm	A++/A+/A	40	1.9
Nextrema 4000-840...+HFSB +LV TWW	64 867...	...51	-	4500 lm	A++/A+/A	40	1.9
Nextrema 4000-840...+HFSB TWW	64 866...	...51	-	4500 lm	A++/A+/A	40	1.9
Nextrema 4000-840...+HFSX +LV TWW	64 868...	...51	-	4500 lm	A++/A+/A	40	1.9
Nextrema 6000-840...+HFS TWW	62 167...	-	...40	6200 lm	A++/A+/A	55	1.9
Nextrema 6000-840...+HFS+LV TWW	62 168...	-	...40	6200 lm	A++/A+/A	55	1.9
Nextrema 6000-840...+LV TWW	62 166...	...51	...40	6200 lm	A++/A+/A	55	1.9
Nextrema 6000-840...TWW	62 165...	...51	...40	6200 lm	A++/A+/A	55	1.9
Nextrema 6000-840...+HFSB +LV TWW	64 870...	...51	-	6200 lm	A++/A+/A	55	1.9
Nextrema 6000-840...+HFSB TWW	64 869...	...51	-	6200 lm	A++/A+/A	55	1.9
Nextrema 6000-840...+HFSX +LV TWW	64 871...	...51	-	6200 lm	A++/A+/A	55	1.9

• IK04/0.5 J 650 °C


Surface-mounted weather-proof luminaires, polycarbonate (PC)



Reference	TOC	...ETDD	...ET		EEC	W	=kg
• Nextrema 4000-840...+HFS TWW PC	62 337...	-	...40	4300 lm	A++/A+/A	40	1.9
Nextrema 4000-840...+HFS+LV TWW PC	62 338...	-	...40	4300 lm	A++/A+/A	40	1.9
Nextrema 4000-840...+LV TWW PC	62 336...	...51	...40	4300 lm	A++/A+/A	40	1.9
Nextrema 4000-840...TWW PC	62 335...	...51	...40	4300 lm	A++/A+/A	40	1.9
Nextrema 4000-840...+HFSB +LV TWW PC	64 873...	...51	-	4300 lm	A++/A+/A	40	1.9
Nextrema 4000-840...+HFSB TWW PC	64 872...	...51	-	4300 lm	A++/A+/A	40	1.9
Nextrema 4000-840...+HFSX +LV TWW PC	64 874...	...51	-	4300 lm	A++/A+/A	40	1.9
Nextrema 6000-840...+HFS TWW PC	62 341...	-	...40	5900 lm	A++/A+/A	55	1.9
Nextrema 6000-840...+HFS+LV TWW PC	62 342...	-	...40	5900 lm	A++/A+/A	55	1.9
Nextrema 6000-840...+LV TWW PC	62 340...	...51	...40	5900 lm	A++/A+/A	55	1.9
Nextrema 6000-840...TWW PC	62 339...	...51	...40	5900 lm	A++/A+/A	55	1.9
Nextrema 6000-840...+HFSB +LV TWW PC	64 876...	...51	-	5900 lm	A++/A+/A	55	1.9
Nextrema 6000-840...+HFSB TWW PC	64 875...	...51	-	5900 lm	A++/A+/A	55	1.9
Nextrema 6000-840...+HFSX +LV TWW PC	64 877...	...51	-	5900 lm	A++/A+/A	55	1.9

• IK08/6 J 850 °C

Mounting accessories



Reference	TOC	Accessory description	=kg
Nextrema ZB ATL	62 354 00	Theft protection	0.1
Nextrema ZB MC	63 102 00	Bracket for suspended mounting	0.1

Sensor remote controls



Reference	TOC	Accessory description	≈kg
LMS HFS RMC	61 229 00	Remote control for Nextrema ON/OFF sensor luminaires	0.1
LMS HFSB/X RMC	64 878 00	Remote control for Nextrema DALI sensor luminaires	0.1

Emergency lights



Reference	TOC	Accessory description	≈kg
Nextrema LED 400 nw EB1h	61 969 00	Emergency light with individual battery system, nominal operating time: 1 hour	1.3
Nextrema LED 400 nw EB3h	61 970 00	Emergency light with individual battery system, nominal operating time: 3 hours	1.3