

Orma



A drive-over uplight whose undisputable strength is its **reduced height**. A **good luminous flux and high protection** make this lighting fixture the ideal partner to illuminate outdoor architecture in a versatile way.

Passive heat dissipation

Anodised aluminium casing or AISI 316 stainless steel casing for high salinity environments

Light management


Partly black silk-screened diffuser to reduce glare

Reduced installation space

Minimum installation space, 42 to 45 mm total height




Orma_R | Drive-over spotlight | powerLED 3 W 350 mA



type		colour			optic	
Steel/Alu	CRI 80	96098	2700 K	363 lm	M	15° 15
			3000 K	390 lm	W	30° 30
			4000 K	414 lm	N	60° 60

89421	99183	98057
ON/OFF 1 - 2 art.	ON/OFF 2 - 4 art.	Outer casing


Orma_R | Drive-over spotlight | powerLED 6 W 350 mA



type		colour			optic	
Steel/Alu	CRI 80	93980	2700 K	726 lm	M	8° 08
			3000 K	780 lm	W	30° 30
			4000 K	828 lm	N	60° 60
						Diff. 00

89421	99183	98399
ON/OFF 1 art.	ON/OFF 1 - 2 art.	Outer casing


Orma_RI | Drive-over spotlight | powerLED 3 W 350 mA



type		colour			optic	
Steel	CRI 80	96100	2700 K	363 lm	M	15° 15
			3000 K	390 lm	W	30° 30
			4000 K	414 lm	N	60° 60

89421	99183	98057
ON/OFF 1 - 2 art.	ON/OFF 2 - 4 art.	Outer casing

Orma_RI | Drive-over spotlight | powerLED 6 W 350 mA



type		colour			optic	
Steel	CRI 80	93993	2700 K	726 lm	M	8° 08
			3000 K	780 lm	W	30° 30
			4000 K	828 lm	N	60° 60
						Diff. 00


89421	99183	98399
ON/OFF 1 art.	ON/OFF 1 - 2 art.	Outer casing

Orma | Outer-casing



type	Ø mm	h. mm	suitable for
PVC	59	55	Orma - Techo67 3W 98057

Orma_Q | Drive-over spotlight | powerLED 3 W 350 mA



type

Steel/Alu CRI 80 **96099**

colour

2700 K	363 lm	M
3000 K	390 lm	W
4000 K	414 lm	N

optic


15°	15
30°	30
60°	60


89421
ON/OFF
1 - 2 art.

99183
ON/OFF
2 - 4 art.

98057
Outer casing

Orma_Q | Drive-over spotlight | powerLED 6 W 350 mA



type

Steel/Alu CRI 80 **93981**

colour

2700 K	726 lm	M
3000 K	780 lm	W
4000 K	828 lm	N

optic


8°	08
30°	30
60°	60
Diff.	00


89421
ON/OFF
1 art.

99183
ON/OFF
1 - 2 art.

98399
Outer casing

Orma_QI | Drive-over spotlight | powerLED 3 W 350 mA



type

Steel CRI 80 **96101**

colour

2700 K	363 lm	M
3000 K	390 lm	W
4000 K	414 lm	N

optic



15°	15
30°	30
60°	60


89421
ON/OFF
1 - 2 art.

99183
ON/OFF
2 - 4 art.

98057
Outer casing

Orma_QI | Drive-over spotlight | powerLED 6 W 350 mA



type

Steel CRI 80 **93992**

colour

2700 K	726 lm	M
3000 K	780 lm	W
4000 K	828 lm	N

optic


8°	08
30°	30
60°	60
Diff.	00


89421
ON/OFF
1 art.

99183
ON/OFF
1 - 2 art.

98399
Outer casing

Orma | Outer-casing



type

PVC

Ø mm

106

h. mm

65

suitable for

Orma 6W

98399