

Concentrica



Concentric light circles or squares that create an eye-catching effect at ground level, making it an excellent, original, discreet, yet highly effective **marker** uplight.

Passive heat dissipation

Anodised aluminium casing

Light management

Single or double circular diffuser in opaline polycarbonate; also available with central mini uplight

Durable appearance

UV-resistant F.O.L.™ system to obtain a uniform brightness of the round diffusers (2.5W and 4W versions) and to effectively limit colour shift over time; additionally, the Aqua-Stop system ensures higher cable protection against water and humidity



Concentrica_R | Drive-over spotlights | topLED 1.4 W 24 V



type		colour			optic	
White	CRI 80 95474	2700 K	54 lm	M	Diff.	00
Black	CRI 80 95475	3000 K	60 lm	W		
Grey	CRI 80 95476	4000 K	63 lm	N		

89488	89179	99332	98291	98292
ON/OFF 1 - 10 art.	ON/OFF 1 - 17 art.	1-10V 1 - 107 art.	Outer casing	Outer casing


Concentrica_R | Drive-over spotlights | topLED 2.6 W 24 V



type		colour			optic	
White	CRI 80 95486	2700 K	216 lm	M	Diff.	00
Black	CRI 80 95487	3000 K	240 lm	W		
Grey	CRI 80 95488	4000 K	252 lm	N		

89488	89179	99332	98315	98317
ON/OFF 1 - 5 art.	ON/OFF 1 - 9 art.	1-10V 1 - 57 art.	Outer casing	Outer casing


Concentrica_R | Drive-over spotlights | topLED 4 W 24 V



type		colour			optic	
White	CRI 80 95501	2700 K	324 lm	M	Diff.	00
Black	CRI 80 95502	3000 K	360 lm	W		
Grey	CRI 80 95503	4000 K	378 lm	N		

89488	89179	99332	98316	98318
ON/OFF 1 - 3 art.	ON/OFF 1 - 6 art.	1-10V 1 - 37 art.	Outer casing	Outer casing

Concentrica_R | Drive-over spotlights | topLED 1.4 W 24 V



type

White	95477
Black	95478
Grey	95479

colour

RGB Z

optic

Diff. 00



99076

IR Remote



99278

DMX



98291

Outer casing



98292

Outer casing

Concentrica_R | Drive-over spotlights | topLED 2.6 W 24 V



type

White	95489
Black	95490
Grey	95491

colour

RGB Z

optic

Diff. 00



99076

IR Remote



99278

DMX



98315

Outer casing



98317

Outer casing

Concentrica_R | Drive-over spotlights | topLED 4 W 24 V



type

White	95504
Black	95505
Grey	95506

colour

RGB Z

optic

Diff. 00



99076

IR Remote



99278

DMX



98316



Outer casing







98318

Outer casing



Concentrica_Q | Drive-over spotlights | topLED 1.4 W 24 V







type		colour			optic	
White	CRI 80 96659	2700 K	54 lm	M	Diff.	00
Black	CRI 80 96660	3000 K	60 lm	W		
Grey	CRI 80 96661	4000 K	63 lm	N		

- 
89488
 ON/OFF
 1 - 10 art.
- 
89179
 ON/OFF
 1 - 17 art.
- 
99332
 1-10V
 1 - 107 art.
- 
98402
 Outer casing



Concentrica_Q | Drive-over spotlights | topLED 2.6 W 24 V







type		colour			optic	
White	CRI 80 96662	2700 K	216 lm	M	Diff.	00
Black	CRI 80 96663	3000 K	240 lm	W		
Grey	CRI 80 96664	4000 K	252 lm	N		

- 
89488
 ON/OFF
 1 - 5 art.
- 
89179
 ON/OFF
 1 - 9 art.
- 
99332
 1-10V
 1 - 60 art.
- 
98403
 Outer casing



Concentrica_Q | Drive-over spotlights | topLED 4 W 24 V



type		colour			optic	
White	CRI 80 96665	2700 K	324 lm	M	Diff.	00
Black	CRI 80 96666	3000 K	360 lm	W		
Grey	CRI 80 96667	4000 K	378 lm	N		

- 
89488
 ON/OFF
 1 - 3 art.
- 
89179
 ON/OFF
 1 - 6 art.
- 
99332
 1-10V
 1 - 37 art.
- 
98404
 Outer casing

Concentrica_Q | Drive-over spotlights | topLED 1.4 W 24 V



type

White	96668
Black	96669
Grey	96670

colour

RGB Z

optic

Diff. 00



99076

IR Remote



99278



DMX



98402

Outer casing

Concentrica_Q | Drive-over spotlights | topLED 2.6 W 24 V



type

White	96671
Black	96672
Grey	96673

colour

RGB Z

optic

Diff. 00



99076

IR Remote



99278



DMX



98403

Outer casing

Concentrica_Q | Drive-over spotlights | topLED 4 W 24 V



type

White	96674
Black	96675
Grey	96676

colour

RGB Z

optic

Diff. 00



99076

IR Remote



99278



DMX



98404

Outer casing

Concentrica_X | Drive-over spotlights | powerLED 1 W + topLED 2,6 W



type		colour			optic	
White	CRI 80 95492	2700 K	337 lm	M	8°	08
Black	CRI 80 95493	3000 K	370 lm	W	15°	15
Grey	CRI 80 95494	4000 K	390 lm	N	30°	30
					60°	60
					Diff.	00



89419
C.C.
ON/OFF
1 - 2 art.



89421
C.C.
ON/OFF
3 - 6 art.



89488
C.V.
ON/OFF
1 - 4 art.



89179
C.V.
ON/OFF
1 - 9 art.




98317
Outer casing



98315
Outer casing

Concentrica_X | Drive-over spotlights | powerLED 1 W + topLED 4 W



type		colour			optic	
White	CRI 80 95507	2700 K	445 lm	M	8°	08
Black	CRI 80 95508	3000 K	490 lm	W	15°	15
Grey	CRI 80 95509	4000 K	516 lm	N	30°	30
					60°	60
					Diff.	00



89419
C.C.
ON/OFF
1 - 2 art.



89421
C.C.
ON/OFF
3 - 6 art.



89488
C.V.
ON/OFF
1 - 3 art.



89179
C.V.
ON/OFF
1 - 6 art.



98316
Outer casing



98318
Outer casing



Concentrica | In-ground installation outer-casing




type	Ø mm	h. mm	suitable for
PVC	43	80	Concentrica_R Ø 42 mm 98292

Concentrica | In-ground installation outer-casing




type	Ø mm	h. mm	suitable for
PVC	84	100	Concentrica_R Ø 76 mm 98317

Concentrica | In-ground installation outer-casing



type	Ø mm	h. mm	suitable for
PVC	108	100	Concentrica_R Ø 100 mm 98318

Concentrica | In-concrete installation outer-casing




type	b. mm	h. mm	suitable for
Anod. Al.	105 x 105	98 / 138	Concentrica_R Ø 42 mm 98291

Concentrica | In-concrete installation outer-casing




type	b. mm	h. mm	suitable for
Anod. Al.	105 x 105	104 / 136	Concentrica_R Ø 76 mm 98315

Concentrica | In-concrete installation outer-casing




type	b. mm	h. mm	suitable for
Anod. Al.	150 x 150	101 / 136	Concentrica_R Ø 100 mm 98316

Concentrica | In-ground installation outer-casing




type	b. mm	h. mm	suitable for	
PVC Steel	52 x 52	102 / 122	Concentrica_Q 42 mm	98402

Concentrica | In-ground installation outer-casing



type	b. mm	h. mm	suitable for	
PVC Steel	84 x 84	107 / 127	Concentrica_Q 42 mm	98403

Concentrica | In-ground installation outer-casing



type	b. mm	h. mm	suitable for	
PVC Steel	100 x 100	107 / 127	Concentrica_Q 94 mm	98404