

# AMON WALL



● AN-96 / Anthracite gray / Textured



- Indoor and outdoor wall-mount fixture, comprising:
- Extruded aluminium profile housing, painted
  - Diffuser in internally frosted extra clear, tempered, flat glass
  - High-transparency polycarbonate lenses for best light transmission
  - Anti-ageing silicone gasket
  - Painted die cast aluminium trims and caps
  - Dimmable driver 1-10 V ballast
  - Aluminium heat sink
  - Stainless steel external screws
  - Painted die cast aluminium bracket for wall mounted applications, featuring ease of installation
  - "Double-emission (B) versions are equipped with two lights in order to provide upward and downward emission "
  - On request, versions with DALI dimming



## AMON WALL A/M

IK08 5J xx5


ATTACCO	POTENZA	CLASSE	☑	CRI	KELVIN	COS φ ≥ 0,9	OTTICA	ANGOLO OTTICA	FLUSSO DELLA SORGENTE	FLUSSO DI APPARECCHIO	L	B	LIFETIME	COLORE/ RAL	CODICE
<b>Power LED - dimmerabile 1-10 V 220-240 V 50/60 Hz</b>															
LED	28 W	I		80	4000	•	A15/M -		3120 lm	1811 lm	70	10	80000 h	●	<b>306311</b>
LED	28 W	I		80	4000	•	A30/M -		3120 lm	1786 lm	70	10	80000 h	●	<b>306312</b>



## AMON WALL B A/M

IK08 5J xx5

ATTACCO	POTENZA	CLASSE	☑	CRI	KELVIN	COS φ ≥ 0,9	OTTICA	ANGOLO OTTICA	FLUSSO DELLA SORGENTE	FLUSSO DI APPARECCHIO	L	B	LIFETIME	COLORE/ RAL	CODICE
<b>Power LED - dimmerabile 1-10 V 220-240 V 50/60 Hz</b>															
LED	56 W	I		80	4000	•	A15/M -		6240 lm	3622 lm	70	10	80000 h	●	<b>306313</b>
LED	56 W	I		80	4000	•	A30/M -		6240 lm	3571 lm	70	10	80000 h	●	<b>306314</b>



## AMON WALL B A/M+S/I

IK08 5J xx5

ATTACCO	POTENZA	CLASSE	☑	CRI	KELVIN	COS φ ≥ 0,9	OTTICA	ANGOLO OTTICA	FLUSSO DELLA SORGENTE	FLUSSO DI APPARECCHIO	L	B	LIFETIME	COLORE/ RAL	CODICE
<b>Power LED - dimmerabile 1-10 V 220-240 V 50/60 Hz</b>															
LED	37 W	I		80	4000	•	A15/M -		4160 lm	2358 lm	70	10	80000 h	●	<b>306315</b>
LED	37 W	I		80	4000	•	A30/M -		4160 lm	2332 lm	70	10	80000 h	●	<b>306316</b>

