Ardilla66





Very compact outdoor wall light **characterized by square design** and available in the version with single and double diffused emission and in the version with combined double diffused emission + 60-degree optics. No external driver required thanks to the Direct-to-the-Power power supply system.


Light management Three combinations available for maximum design flexibility

Direct-to-the-power Directly connected to the mains voltage with no external drivers required



Ardilla66 Single emission | Wall light | topLED 4.5 W 190-240 V AC






type		
White	CRI 80	97838
Black	CRI 80	97839
Grey	CRI 80	97840
Cor-Ten	CRI 80	97841



colour			optic	
3000 K	360 lm	w	Diff.	00
4000 K	475 lm	Ν		

Ardilla66 Double emission | Wall light | topLED 9 W 190-240 V AC





type		
White	CRI 80	97842
Black	CRI 80	97843
Grey	CRI 80	97844
Cor-Ten	CRI 80	97845

C.) 🕑 🛨	C.V. [IK05 IP66 I	
colour			optic	
3000 K	720 lm	w	Diff.	00
4000 K	950 lm	N		

Ardilla66 Double emission | Wall light | topLED 9 W 190-240 V AC





type		
White	CRI 80	97884
Black	CRI 80	97885
Grey	CRI 80	97886
Cor-Ten	CRI 80	97887

()		C.V.	05 IP66 I	
colour			optic	
3000 K	720 lm	w	Diff.+60°	61

Ν

4000 K

950 lm

