

- Luminaire for installation on wall – surface mounted.
- Configuration: turned aluminium body (EN AW6060 alloy) and AISI 316L stainless steel fixing bracket. Glass diffuser: extra clear with silkscreen border, fixed to the body by a double-sided tape.
- Double layer coating for high resistance to corrosion: the aluminium components are painted with a double coat using powders that are compliant with QUALICOAT standards: a first layer of epoxy powder (with excellent chemical and mechanical resistance) and a second finishing layer of polyester powder (resistant to UV rays and atmospheric agents). The entire painting process of the aluminium fitting starts from components that have been sandblasted in advance to make the surface more porous and increase the adherence of the paint. Ares effects alkaline and acid washing to clean the surfaces completely, then rinses with demineralised water to remove any residue particles, subsequently a chemical conversion treatment is done to protect against rusting.
- Protection rating: IP65.
- In compliance with EN 60598-1 standards.
- Class of insulation: III.
- Installation: the luminaire is supplied with a piece of cable (approx. 250mm) for an easy-to-make connection and it is equipped with a dc/dc resin-coated converter that removes electromagnetic interference. The luminaire is protected against polarity reversal and sudden voltage peak. Parallel wiring required.
- We recommend the use of a connection system with a protection degree greater than or equal to the protection degree of the luminaire.

## EU Regulation 874/2012 - Illumination equipment energy classes



**LED VERSION:**  
Class A/A+/A++  
Luminaire supplied with integrated LED modules that cannot be replaced



.1 White



.6 Grey



.3 Anthracite



.4 Black



.18 Deep Brown



Wall fitting



Pre-wired with approx 250mm of cable.






Remote device required.



Protection against impact.  
IK 05 - 0,70 joule



### Delta Power LED / Unidirectional - Narrow Beam 10°



#### 507002 **A A+ A++**

NATURAL WHITE 4000K  
POWER LED  
2,2W/24Vdc  
Total power 3,4W  
Lm LED 198 ≠ Lm OUTPUT 138  
CRI>80

Remote electronic power supply to be ordered





#### 507003 **A A+ A++**

WARM WHITE 3000K  
POWER LED  
2,2W/24Vdc  
Total power 3,4W  
Lm LED 182 ≠ Lm OUTPUT 127  
CRI>80

Remote electronic power supply to be ordered



### Delta Power LED / Unidirectional - Medium Beam 30°



#### 507012 **A A+ A++**

NATURAL WHITE 4000K  
POWER LED  
2,2W/24Vdc  
Total power 3,4W  
Lm LED 198 ≠ Lm OUTPUT 125  
CRI>80

Remote electronic power supply to be ordered






#### 507013 **A A+ A++**

WARM WHITE 3000K  
POWER LED  
2,2W/24Vdc  
Total power 3,4W  
Lm LED 182 ≠ Lm OUTPUT 114  
CRI>80

Remote electronic power supply to be ordered



### Delta Power LED / Unidirectional - Narrow Beam 10°



#### 507022 **A A+ A++**

NATURAL WHITE 4000K  
POWER LEDs  
3,3W/24Vdc  
Total power 4,5W  
Lm LED 360 ≠ Lm OUTPUT 258  
CRI>80

Remote electronic power supply to be ordered



#### 507023 **A A+ A++**

WARM WHITE 3000K  
POWER LEDs  
3,3W/24Vdc  
Total power 4,5W  
Lm LED 330 ≠ Lm OUTPUT 236  
CRI>80

Remote electronic power supply to be ordered



### Delta Power LED / Unidirectional - Medium Beam 30°



#### 507032 **A A+ A++**

NATURAL WHITE 4000K  
POWER LEDs  
3,3W/24Vdc  
Total power 4,5W  
Lm LED 360 ≠ Lm OUTPUT 207  
CRI>80


Remote electronic power supply to be ordered




#### 507033 **A A+ A++**

WARM WHITE 3000K  
POWER LEDs  
3,3W/24Vdc  
Total power 4,5W  
Lm LED 330 ≠ Lm OUTPUT 189  
CRI>80

Remote electronic power supply to be ordered





### Delta Power LED / Bidirectional - Narrow Beam 10°



#### 507102 **A A+ A++**

NATURAL WHITE 4000K  
POWER LEDs  
4,4W/24Vdc  
Total power 6,8W  
Lm LED 2x198 ≠ Lm OUTPUT 2x138  
CRI>80


Remote electronic power supply to be ordered




#### 507103 **A A+ A++**

WARM WHITE 3000K  
POWER LEDs  
4,4W/24Vdc  
Total power 6,8W  
Lm LED 2x182 ≠ Lm OUTPUT 2x127  
CRI>80

Remote electronic power supply to be ordered





### Delta Power LED / Bidirectional - Medium Beam 30°



#### 507112 **A A+ A++**

NATURAL WHITE 4000K  
POWER LEDs  
4,4W/24Vdc  
Total power 6,8W  
Lm LED 2x198 ≠ Lm OUTPUT 2x125  
CRI>80


Remote electronic power supply to be ordered






#### 507113 **A A+ A++**

WARM WHITE 3000K  
POWER LEDs  
4,4W/24Vdc  
Total power 6,8W  
Lm LED 2x182 ≠ Lm OUTPUT 2x114  
CRI>80

Remote electronic power supply to be ordered




## Delta Power LED / Bidirectional - Narrow Beam 10°



### 507122 A A+ A++

NATURAL WHITE 4000K  
 POWER LEDs  
 6,6W/24Vdc  
 Total power 9W  
 Lm LED 2x360 ≠ Lm OUTPUT 2x258  
 CRI>80  
 Remote electronic power supply  
 to be ordered






m	lux	
	Max	Med
1.00	4368	2691
2.00	1092	673
3.00	485	299
4.00	273	168
5.00	175	108

$\alpha = 5.0^\circ + 5.0^\circ$        $\beta = 5.0^\circ + 5.0^\circ$

### 507123 A A+ A++


WARM WHITE 3000K  
 POWER LEDs  
 6,6W/24Vdc  
 Total power 9W  
 Lm LED 2x330 ≠ Lm OUTPUT 2x236  
 CRI>80  
 Remote electronic power supply  
 to be ordered

## Delta Power LED / Bidirectional - Medium Beam 30°



### 507132 A A+ A++

NATURAL WHITE 4000K  
 POWER LEDs  
 6,6W/24Vdc  
 Total power 9W  
 Lm LED 2x360 ≠ Lm OUTPUT 2x207  
 CRI>80  
 Remote electronic power supply  
 to be ordered



m	lux	
	Max	Med
1.00	523	317
2.00	131	79
3.00	58	35
4.00	33	20
5.00	21	13

$\alpha = 15.0^\circ + 15.0^\circ$        $\beta = 15.0^\circ + 15.0^\circ$

### 507133 A A+ A++


WARM WHITE 3000K  
 POWER LEDs  
 6,6W/24Vdc  
 Total power 9W  
 Lm LED 2x330 ≠ Lm OUTPUT 2x189  
 CRI>80  
 Remote electronic power supply  
 to be ordered



**Accessories: Delta**


**150**

POWER SUPPLY DUAL FUNCTION  
Vout 24Vdc: 8W/100÷240V  
Iout 350mA: 6x1W/100÷240V  
IP20 CLASS II SELV EQ.




**106**

POWER SUPPLY DUAL FUNCTION  
Vout 24Vdc: 8W/100÷240V  
Iout 350mA: 6x1W/100÷240V  
IP65 CLASS II SELV EQ.




**87**

POWER SUPPLY 10W/110÷240V -  
24Vdc IP20 CLASS II SELV.




**175**

POWER SUPPLY 10W/110÷240V - 24Vdc  
IP67 CLASS II SELV.




**147**

POWER SUPPLY 20W/220÷240V - 24Vdc  
IP67 CLASS II SELV.




**155**

POWER SUPPLY 50W/120÷240V - 24Vdc  
IP67 CLASS II SELV.



**110**

POWER SUPPLY 70W/220÷240V - 24Vdc  
IP67 CLASS II SELV EQ.



acc. code ▶	150	106	87	175	147	155	110
prod. code ▼							
507002	1	1	2	2	3	9	17
507003	1	1	2	2	3	9	17
507012	1	1	2	2	3	9	17
507013	1	1	2	2	3	9	17
507022	1	1	2	2		7	14
507023	1	1	2	2		7	14
507032	1	1	2	2		7	14
507033	1	1	2	2		7	14
507102			1	1	2	5	8
507103			1	1	2	5	8
507112			1	1	2	5	8
507113			1	1	2	5	8
507122			1	1		3	7
507123			1	1		3	7
507132			1	1		3	7
507133			1	1		3	7

Max fixtures for each power supply (Vin 220÷240). Data in the chart are provided as a guide only. Please verify according to your installation.