

Angular




A powerful spotlight with a sleek minimalist look. The **tilting movement up to 90°** is supported by a practical **degree indicator** for precise tilt adjustment. The arrayLED source ensures efficient clean lighting featuring high performances.

Passive heat dissipation
Aluminium casing

Light management
Three levels of light performances available, based on the customer's needs




Angular_1 | Track luminaires | 180-300 V | arrayLED 35 W 950 mA




| type | | colour | | | optic | |
|-------|---------------------|--------|---------|----------|-------|-----------|
| White | CRI 95 91247 | 2700 K | 3064 lm | M | 15° | 15 |
| Black | CRI 95 91256 | 3000 K | 3291 lm | W | 30° | 30 |
| Grey | CRI 95 91258 | 4000 K | 3519 lm | N | 60° | 60 |
| White | CRI 80 91259 | 2700 K | 4051 lm | M | 15° | 15 |
| Black | CRI 80 91267 | 3000 K | 4355 lm | W | 30° | 30 |
| Grey | CRI 80 91268 | 4000 K | 4659 lm | N | 60° | 60 |

Angular_1 DALI | Track luminaires | 180-300 V | arrayLED 20 W 580 mA




| type | | colour | | | optic | |
|-------|---------------------|--------|---------|----------|-------|-----------|
| White | CRI 95 91611 | 3000 K | 2062 lm | W | 15° | 15 |
| Black | CRI 95 91612 | 4000 K | 2214 lm | N | 30° | 30 |
| Grey | CRI 95 91613 | | | | 60° | 60 |

Angular_2 | Track luminaires | 180-300 V | arrayLED 35 W 950 mA




| type | | colour | | | optic | |
|-------|---------------------|--------|---------|----------|-------|-----------|
| White | CRI 95 95869 | 2700 K | 3169 lm | M | 10° | 10 |
| Black | CRI 95 95870 | 3000 K | 3407 lm | W | 30° | 30 |
| Grey | CRI 95 95871 | 4000 K | 3644 lm | N | 60° | 60 |
| White | CRI 80 95881 | 2700 K | 4051 lm | M | 10° | 10 |
| Black | CRI 80 95882 | 3000 K | 4355 lm | W | 30° | 30 |
| Grey | CRI 80 95883 | 4000 K | 4659 lm | N | 60° | 60 |

Angular_2 | Track luminaires | 180-300 V | arrayLED 50 W 1300 mA



| type | | colour | | | optic | |
|-------|---------------------|--------|---------|----------|-------|-----------|
| White | CRI 95 95872 | 2700 K | 4015 lm | M | 10° | 10 |
| Black | CRI 95 95873 | 3000 K | 4310 lm | W | 30° | 30 |
| Grey | CRI 95 95874 | 4000 K | 4611 lm | N | 60° | 60 |
| White | CRI 80 95884 | 2700 K | 5300 lm | M | 10° | 10 |
| Black | CRI 80 95885 | 3000 K | 5695 lm | W | 30° | 30 |
| Grey | CRI 80 95886 | 4000 K | 6090 lm | N | 60° | 60 |

Angular_2 DALI | Track luminaires | 180-300 V | arrayLED 45 W 1200 mA



| type | | colour | | | optic | |
|-------|---------------------|--------|---------|----------|-------|-----------|
| White | CRI 95 91608 | 3000 K | 4070 lm | W | 10° | 10 |
| Black | CRI 95 91609 | 4000 K | 4354 lm | N | 30° | 30 |
| Grey | CRI 95 91610 | | | | 60° | 60 |

Angular_1 | Optics



15° optics

Chrome 98524



diffuser

Transp. 98515

Opaline 98516



30° optics

Chrome 98525



60° optics

Chrome 98526

Angular_1 | Accessories



blade

Black 98521



anti-glare tube

Black 98519



honeycomb louvre

Black 98522



flap

Black 98523



cross louvre

Black 98520



anti-glare screen

Black 98518

Angular_2 | Optics



10° optics

Chrome 98259



30° optics

Chrome 98260



60° optics

Chrome 98261

Angular_2 | Accessories



blade

Black 98517



anti-glare tube

Black 98503



honeycomb louvre

Black 98511



flap

Black 98505



cross louvre

Black 98506



anti-glare screen

Black 98504



