

# OnLED


## RECESSEDS

### IP33 EXT



#### EN

Adjustable aluminium recessed spotlight, designed for high performance LED with a choice of 2 different beam reflectors. Remote LED driver included and optional dimmable IGBT/TRIAC, 1-10V, PUSH or DALI version available. Also available with IP65 protection index against water jets.



850°



35°

150



Ø75

onLED

**LED**



230V ≈ 8W > 600lm

**OLDX A 08 . . . . B ..**

#### LED CONTROL

	<b>N</b>	No Dimmable	OLDX	A	..	<b>N</b>	.	.	.	..
	<b>C</b>	Dimmable IGBT / Triac	OLDX	A	..	<b>C</b>	.	.	.	..
	<b>F</b>	Dimmable 1-10V / Push	OLDX	A	..	<b>F</b>	.	.	.	..
	<b>D</b>	Dimmable Dali	OLDX	A	..	<b>D</b>	.	.	.	..

#### LED COLOUR TEMPERATURE

	<b>3</b>	3000° K	OLDX	A	..	.	.	<b>3</b>	.	..
	<b>4</b>	4000° K	OLDX	A	..	.	.	<b>4</b>	.	..

#### LED BEAM ANGLE

	<b>3</b>	Medium	OLDX	A	..	.	.	.	<b>3</b>	..
	<b>6</b>	Flood	OLDX	A	..	.	.	.	<b>6</b>	..

#### LED COMPLEMENTS

	<b>X</b>	Clear Diffuser	OLDX	A	..	.	.	.	.	<b>B</b> ..
--	----------	----------------	------	---	----	---	---	---	---	-------------

#### COLOURS

	<b>WS</b>	Satin White	OLDX	A	..	.	.	.	.	<b>WS</b>
	<b>BA</b>	Brushed Aluminium	OLDX	A	..	.	.	.	.	<b>BA</b>



# OnLED IP65


## RECESSEDS

### IP65



#### EN

Adjustable aluminium recessed spotlight, designed for high performance LED with a choice of 2 different beam reflectors. Remote LED driver included and optional dimmable IGBT/TRIAC, 1-10V, PUSH or DALI version available. Also available with IP65 protection index against water jets.



onLED IP65

**LED** 230V ≈ 8W > 600lm **OL65 A 08 • 3 3 B WS**

#### LED CONTROL

	<b>N</b>	No Dimmable	OL65	A	..	<b>N</b>	•	•	•	•	..
	<b>C</b>	Dimmable IGBT / Triac	OL65	A	..	<b>C</b>	•	•	•	•	..
	<b>F</b>	Dimmable 1-10V / Push	OL65	A	..	<b>F</b>	•	•	•	•	..
	<b>D</b>	Dimmable Dali	OL65	A	..	<b>D</b>	•	•	•	•	..

#### LED COLOUR TEMPERATURE

	<b>3</b>	3000° K	OL65	A	..	•	<b>3</b>	•	•	•	..
--	----------	---------	------	---	----	---	----------	---	---	---	----

#### LED BEAM ANGLE

	<b>3</b>	Medium	OL65	A	..	•	•	•	<b>3</b>	•	..
--	----------	--------	------	---	----	---	---	---	----------	---	----

#### LED COMPLEMENTS

	<b>B</b>	Clear Diffuser	OL65	A	..	•	•	•	•	<b>B</b>	..
--	----------	----------------	------	---	----	---	---	---	---	----------	----

#### COLOURS

	<b>WS</b>	Satin White	OL65	A	..	•	•	•	•	•	<b>WS</b>
--	-----------	-------------	------	---	----	---	---	---	---	---	-----------



# OnLED Q


## RECESSEDS

### IP33 EXT



#### EN

Adjustable aluminium recessed spotlight, designed for high performance LED with a choice of 2 different beam reflectors. Remote LED driver included and optional dimmable IGBT/TRIAC, 1-10V, PUSH or DALI version available.



850°

150 *db* Ø75

onLED Q

**LED** 230V ≈ 8W > 600lm **OLDQ A 08 . . . B ..**

#### LED CONTROL

	<b>N</b>	No Dimmable	OLDQ A .. <b>N</b> . . . ..
	<b>C</b>	Dimmable IGBT / Triac	OLDQ A .. <b>C</b> . . . ..
	<b>F</b>	Dimmable 1-10V / Push	OLDQ A .. <b>F</b> . . . ..
	<b>D</b>	Dimmable Dali	OLDQ A .. <b>D</b> . . . ..

#### LED COLOUR TEMPERATURE

	<b>3</b>	3000° K	OLDQ A .. . <b>3</b> . . . ..
	<b>4</b>	4000° K	OLDQ A .. . <b>4</b> . . . ..

#### LED BEAM ANGLE

	<b>3</b>	Medium	OLDQ A .. . . <b>3</b> . . .
	<b>6</b>	Flood	OLDQ A .. . . <b>6</b> . . .

#### LED COMPLEMENTS

	<b>X</b>	Clear Diffuser	OLDQ A .. . . . <b>B</b> ..
--	----------	----------------	-----------------------------

#### COLOURS

	<b>WS</b>	Satin White	OLDQ A .. . . . . <b>WS</b>
	<b>BA</b>	Brushed Aluminium	OLDQ A .. . . . . <b>BA</b>

