



KYCLOS



L80 B10 >50 000h • CRI 85

MOC	ŹRÓDŁO	KĄT ROŚYEU	[kg]	KOLOR	KOD
POWER	LAMP	ANGLE OF LIGHT BEAM	[kg]	COLOUR	CODE
KYCLOS	51 W LED 6400 lm 3000 K	30°	1,9	■	IV725-562-16
	51 W LED 6400 lm 3000 K	30°	1,9	□	IV725-562-21
	39 W LED 4900 lm 3000 K	30°	1,7	■	IV725-663-16
KYCLOS POWER	39 W LED 4900 lm 3000 K	30°	1,7	□	IV725-663-21
	75 W LED 9900 lm 3000 K	25°	3,5	□	IV719-261-21
	75 W LED 9900 lm 3000 K	25°	3,5	■	IV719-261-52



KYCLOS



KYCLOS POWER



MINI KYCLOS

MINI KYCLOS



L80 B10 >50 000h • CRI 80

MOC	ŹRÓDŁO	KĄT ROŚYEU	[kg]	KOLOR	KOD
POWER	LAMP	ANGLE OF LIGHT BEAM	[kg]	COLOUR	CODE
MINI KYCLOS	18 W LED 2400 lm 3000 K	30°	0,9	■	IV717-161-16
	18 W LED 2400 lm 3000 K	30°	0,9	□	IV717-161-21
	18 W LED 2400 lm 3000 K	30°	0,9	■	IV717-161-52
	26 W LED 3350 lm 3000 K	30°	0,9	■	IV717-261-16
	26 W LED 3350 lm 3000 K	30°	0,9	□	IV717-261-21
	26 W LED 3350 lm 3000 K	30°	0,9	■	IV717-261-52
MINI KYCLOS 230	19 W LED 2000 lm 3000 K	38°	0,6	■	IV717-661-16
	19 W LED 2000 lm 3000 K	38°	0,6	□	IV717-661-21
	19 W LED 2000 lm 3000 K	38°	0,6	■	IV717-661-52

KYCLOS

Wykonanie: odlew aluminiowy malowany farbą poliestrowo-epoksydową. Przód oprawy wykonany z przezroczystego lub malowanego poliwęglanu. Metalizowany odbłyśnik z materiału termoplastycznego.

Montaż: do szynoprzewodu 3-fazowego, wersja z bazą na zapytanie

Akcesoria: odbłyśniki do regulacji kąta rozsyłu


Zasilanie: 220 V - 240 V

Materials: epoxy-polyester painted die-cast aluminum. Front made of transparent or painted polycarbonate. Metalized reflector made of thermo plastic material


Installation: to electrical tracks, on a base version - on request

Accessories: reflector for beam angle regulation

Power supply: 220 V - 240 V







KYCLOS 70°



KYCLOS 30°

AKCESORIA ACCESSORIES

KOD CODE	2000 lm	2400 lm	3350 lm	4900 lm	6400 lm	9900 lm
IV28-3140-51	20°	17°	17°	17°	17°	-
IV28-3142-51	-	-	-	-	-	35°
IV28-3138-51	60°	55°	55°	55°	55°	60°
IV28-3141-31	70°	70°	70°	70°	70°	70°



KYCLOS
Wersja z podstawą do sufitu na zapytanie
Version with base on request