

NOWOŚĆ




ROMA IP54 LED 600x600



ROMA IP54 LED 300x1200

ROMA IP54 LED



L80 B10 >54 000h • SDCM 3 • LLMF 89% • CRI 83

MOC	ŹRÓDŁO	STRUMIEN OPRAWY MPRM	SKUTECZNOŚĆ OPRAWY MPRM	[kg]	KOLOR	INFO	KOD
POWER	LAMP	FIXTURE'S LUMINOUS POWER MPRM	FIXTURE'S EFFICACY MPRM	[kg]	COLOUR	INFO	CODE
38 W	LED 3000 K	4120 lm	108 lm/W	4,6	□	OPAL	PX3715350
38 W	LED 4000 K	4250 lm	112 lm/W	4,6	□	OPAL	PX3715358
43 W	LED 3000 K	4380 lm	102 lm/W	5,4	□	OPAL	PX3715366
43 W	LED 4000 K	4520 lm	105 lm/W	5,4	□	OPAL	PX3715374


ROMA IP54 LED

Wykonanie: obudowa z blachy stalowej malowanej elektrostatycznie (w standardzie kolor biały), klosz OPAL z PMMA
Montaż: do sufitów 600x600
Zasilanie: 220 V - 240 V

Materials: powder painted housing made of galvanized steel sheets (standard color: white), OPAL diffuser made of PMMA
Installation: into modular ceilings 600x600
Power supply: 220 V - 240 V

WYMIARY
DIMENSIONS

MOC	INFO	L	W	H
POWER	INFO	[mm]	[mm]	[mm]
38 W	OPAL 600x600	595	595	80
43 W	OPAL 300x1200	295	1195	80



ROMA IP54 LED

