

SANESCA LED

LED WALL LUMINAIRE





LIGHT AND SIMPLICITY FOR THE CARE SECTOR

- Can be used as a pure wall luminaire or with function module above the patient bed.
- Modular design enables the integration of sockets, data modules, nurse call function and other functions.
- Human Centric Lighting, combined with reliable product quality ensure application-compliant illumination, with high well-being and health factor.
- An ideal energy and cost-efficient lighting solution for the easy care sector.



> 50,000 h



switchable and dimmable (DALI), switchable



White-white control



Maximum flexibility and functionality



General and reading light



LED wall luminaires with indirect light distribution






IP40

Reference	TOC	...ETDD	...ET		EEC	W	≈kg
White							
• Sanesca W1 LED 2000-830...01	63 718...	...51	...40	1900 lm	A++/A+/A	20	3.9
Sanesca W1 LED 2000-840...01	63 372...	...51	...40	2000 lm	A++/A+/A	20	3.9
Silver-grey							
Sanesca W1 LED 2000-830...03	63 719...	...51	...40	1900 lm	A++/A+/A	20	3.9
Sanesca W1 LED 2000-840...03	63 373...	...51	...40	2000 lm	A++/A+/A	20	3.9

• IK02/0.2 J 650 °C



LED wall luminaires with indirect-direct light distribution



Reference	TOC	...ETDD	...ET		EEC	W	=kg
White, LED for colour temperature-adjustable lighting							
• SanescaAct W2 4600...830 01	64 480...	...51	-	4600 lm	A++/A+/A	40	4.7
SanescaAct W2 4600...840 01	64 481...	...51	-	4600 lm	A++/A+/A	40	4.7
White, LED							
Sanesca W2 LED 2600-830...01	63 374...	...51	...40	2500 lm	A++/A+/A	26	3.9
Sanesca W2 LED 2600-840...01	63 375...	...51	...40	2600 lm	A++/A+/A	26	3.9
Sanesca W2 LED 4600-830...01	63 360...	...51	...40	4600 lm	A++/A+/A	48	3.9
Sanesca W2 LED 4600-840...01	63 361...	...51	...40	4800 lm	A++/A+/A	48	3.9
Silver-grey, LED for colour temperature-adjustable lighting							
SanescaAct W2 4600...830 03	64 482...	...51	-	4600 lm	A++/A+/A	40	4.7
SanescaAct W2 4600...840 03	64 483...	...51	-	4600 lm	A++/A+/A	40	4.7
Silver-grey, LED							
Sanesca W2 LED 2600-830...03	63 376...	...51	...40	2500 lm	A++/A+/A	26	3.9
Sanesca W2 LED 2600-840...03	63 377...	...51	...40	2600 lm	A++/A+/A	26	3.9
Sanesca W2 LED 4600-830...03	63 362...	...51	...40	4600 lm	A++/A+/A	48	3.9
Sanesca W2 LED 4600-840...03	63 363...	...51	...40	4800 lm	A++/A+/A	48	3.9

• IK02/0.2 J 650 °C

LED wall luminaires with indirect light distribution (room and night-light) and direct light distribution (reading light)





CE IP40

Reference	TOC	...ETDD	...ET		EEC	W	≈kg
White, LED							
• Sanesca W3 LED 4600-830...01	63 806...	...51	...40	4600 lm	A++/A+/A	48	4.5
Sanesca W3 LED 4600-840...01	63 807...	...51	...40	4800 lm	A++/A+/A	48	4.5
Silver-grey, LED							
Sanesca W3 LED 4600-830...03	63 808...	...51	...40	4600 lm	A++/A+/A	48	4.5
Sanesca W3 LED 4600-840...03	63 809...	...51	...40	4800 lm	A++/A+/A	48	4.5

• IK02/0.2 J 650 °C

LED wall luminaires with indirect light distribution (room and night-light) and direct light distribution (reading light) with rocker switch and plug socket





CE IP40

Reference	TOC	...ETDD	...ET		EEC	W	≈kg
White, LED							
• Sanesca W3-S1/R LED 4600-830...01	63 364...	...51	...40	4600 lm	A++/A+/A	48	5.9
Sanesca W3-S1/R LED 4600-840...01	63 365...	...51	...40	4800 lm	A++/A+/A	48	5.9
Silver-grey, LED							
Sanesca W3-S1/R LED 4600-830...03	63 366...	...51	...40	4600 lm	A++/A+/A	48	5.9
Sanesca W3-S1/R LED 4600-840...03	63 367...	...51	...40	4800 lm	A++/A+/A	48	5.9

• IK02/0.2 J 650 °C

LED wall luminaires with indirect light distribution (room and night-light) and direct light distribution (reading light) with pull-cord switch and plug socket





CE IP40

Reference	TOC	...ETDD	...ET		EEC	W	=kg
White, LED							
• Sanesca W3-S2/R LED 4600-830...01	63 368...	...51	...40	4600 lm	A++/A+/A	48	4.5
Sanesca W3-S2/R LED 4600-840...01	63 369...	...51	...40	4800 lm	A++/A+/A	48	4.5
Silver-grey, LED							
Sanesca W3-S2/R LED 4600-830...03	63 370...	...51	...40	4600 lm	A++/A+/A	48	4.5
Sanesca W3-S2/R LED 4600-840...03	63 371...	...51	...40	4800 lm	A++/A+/A	48	4.5

• IK02/0.2 J 650 °C

LED wall luminaires with indirect light distribution (room and night-light) and direct light distribution (reading/inspection light)



CE IP40

Reference ¹⁾	TOC	...ET		EEC	W	=kg
Silver-grey, LED						
• Sanesca W4-L20/R LED 4900-830...03	64 977...	...40	4900 lm	A++/A+/A	51	6.3

¹⁾ Individual configuration on request

• IK02/0.2 J 650 °C