



SQUARE LED



L90 B10 >54 000h • SDCM 3 • LLMF 89% • CRI 80

MOC	ŹRÓDŁO	STRUMIEN OPRAWY	SKUTECZNOŚĆ OPRAWY	[kg]	KOLOR	INFO	KOD
POWER	LAMP	LUMINAIRE'S LUMINOUS FLUX	LUMINAIRE'S EFFICACY	[kg]	COLOUR	INFO	CODE
38 W	LED 3000 K	4280 lm	112 lm/W	5,5	□	600x600; G/K	PX4059501
38 W	LED 4000 K	4370 lm	115 lm/W	5,5	□	600x600; G/K	PX4059508
38 W	LED 3000 K	4280 lm	112 lm/W	6,9	□	NT	PX4059515
38 W	LED 4000 K	4370 lm	115 lm/W	6,9	□	NT	PX4059522



SQUARE LED G/K



SQUARE LED NT



Biurowiec
An office building

SQUARE LED

Wykonanie: ramka z profilu aluminiowego oraz obudowa z blachy stalowej ocynkowanej malowanej elektrostatycznie w kolorze białym. Klosz z płyty OPAL z PMMA.
Uwaga: w wersjach wpuszczanych centralnie umieszczony panel sufitowy nie wchodzi w zakres zamówienia, należy go wykonać z płyty montowanego stropu.
Montaż: w sufitach podwieszanych 600x600 o widocznej konstrukcji nośnej, G/K, nastropowy
Zasilanie: 220 V - 240 V

Materials: frame of aluminum profile; body of galvanized steel sheet, powder painted in white colour; OPAL diffuser of PMMA.
Attention: in recessed versions centrally mounted ceiling panel is not part of a luminaire. It should be made of original ceiling panel.
Installation: into modular ceiling 600x600 with a visible supported structure, into plaster-cardboard ceiling or surface mounted
Power supply: 220 V - 240 V

WMIARY DIMENSIONS

MOC	L	W	H	C	D
POWER	[mm]	[mm]	[mm]	[mm]	[mm]
38 W LED	595	595	75	585	585
38 W LED NT	595	595	75	-	-

