

# Cut



A path-marker recessed spotlight with tilted emission and an ultra-thin round or square shape for a **pleasant delicate appearance**. Fitted with internal anti-suction system.

**Passive heat dissipation**


Aluminium casing

**Light distribution**

Very narrow tilted emission for a functional yet pleasant effect



**Cut\_R** | Path-marker | powerLED 2 W 630 mA



52

**type**

White	CRI 80	<b>92513</b>
Grey	CRI 80	<b>92514</b>

**colour**

3000 K	208 lm	<b>W</b>
4000 K	222 lm	<b>N</b>
5000 K	253 lm	<b>C</b>
Blue		<b>B</b>

R - G - Y on request

**optic**

5°	<b>05</b>
----	-----------



**89420**  
ON/OFF  
1 - 2 art.



**99179**  
ON/OFF  
3 - 6 art.




**99186**  
ON/OFF  
6 - 12 art.



**84338**  
Outer casing

**Cut\_Q** | Path-marker | powerLED 2 W 630 mA



52

**type**

White	CRI 80	<b>92558</b>
Grey	CRI 80	<b>92559</b>

**colour**

3000 K	208 lm	<b>W</b>
4000 K	222 lm	<b>N</b>
5000 K	253 lm	<b>C</b>
Blue		<b>B</b>

R - G - Y on request

**optic**

5°	<b>05</b>
----	-----------



**89420**  
ON/OFF  
1 - 2 art.



**99179**  
ON/OFF  
3 - 6 art.



**99186**  
ON/OFF  
6 - 12 art.



**84338**  
Outer casing

