

Ice-Cut



A light profile providing total diffusion by means of a translucent polycarbonate extruded casing. **Intensity is perfectly distributed in just 10 mm of width**, thus resulting in much easier installation.

Comfortable light

Intensity is perfectly distributed in just 10 mm of width

Uninterrupted light

Cable outlet located on the lower side to allow for the creation of lines of light

Versatility


Customizable article available in different lengths

1 : 1

Actual size




Ice_Cut | Linear profiles | topLED 6 W 24 V



type		colour			optic	
Opaline	CRI 95	97846	3000 K	373 lm	W	Diff. 00
			4000 K	409 lm	N	
Opaline	CRI 80	95436	3000 K	439 lm	W	Diff. 00
			4000 K	478 lm	N	
			2700 K	421 lm	M	

89487	84829	99332	98398	Cables
ON/OFF 1 - 2 art.	ON/OFF 1 - 4 art.	1-10V 1 - 25 art.	2 x Fixing clips	815


Ice_Cut | Linear profiles | topLED 12 W 24 V



type		colour			optic	
Opaline	CRI 95	97847	3000 K	746 lm	W	Diff. 00
			4000 K	818 lm	N	
Opaline	CRI 80	95437	3000 K	877 lm	W	Diff. 00
			4000 K	956 lm	N	
			2700 K	841 lm	M	

89487	84829	99332	98398	Cables
ON/OFF 1 art.	ON/OFF 1 - 2 art.	1-10V 1 - 12 art.	2 x Fixing clips	815


Ice_Cut | Linear profiles | topLED 18 W 24 V



type		colour			optic	
Opaline	CRI 95	97848	3000 K	1119 lm	W	Diff. 00
			4000 K	1227 lm	N	
Opaline	CRI 80	95438	3000 K	1315 lm	W	Diff. 00
			4000 K	1434 lm	N	
			2700 K	1261 lm	M	

84829	89359	99332	98398	Cables
ON/OFF 1 art.	ON/OFF 1 - 2 art.	1-10V 1 - 8 art.	2 x Fixing clips	815

Ice_Cut | Linear profiles | topLED 24 W 24 V



type		colour			optic	
Opaline	CRI 95	97849	3000 K	1492 lm	W	Diff. 00
			4000 K	1636 lm	N	
Opaline	CRI 80	95822	3000 K	1753 lm	W	Diff. 00
			4000 K	1912 lm	N	
			2700 K	1681 lm	M	

84829	99331	99332	98398	Cables
ON/OFF 1 art.	ON/OFF 1 - 6 art.	1-10V 1 - 6 art.	2 x Fixing clips	815

