

MK68


Materials

Polycarbonate body

AISI 316L stainless steel/polycarbonate closures



MK68_R | Underwater luminaires | 12 V DC | topLED



694 mm - 11W DC	Cct	lm S - D	Optic
Transp. 82642	W 3000	1470 - On req	36 Diffused
	N 4000	1538 - On req	
	C 6000	1538 - On req	

694 mm - 11W DC	Cct	lm S - D	Optic
Opaline 82646	W 3000	1470 - On req	00 General
	N 4000	1538 - On req	
	C 6000	1538 - On req	

Electronics

83010	83013	83012	83015
ON/OFF 1 - 5 art. p 150 x l 60 x h 35	ON/OFF 1 - 13 art. p 150 x l 60 x h 35	DALI 1 - 5 art. p 191 x l 63 x h 38	DALI 1 - 10 art. p 220 x l 71 x h 38


1290 mm - 20W DC	Cct	lm S - D	Optic
Transp. 82644	W 3000	2940 - On req	36 Diffused
	N 4000	3076 - On req	
	C 6000	3076 - On req	

1290 mm - 20W DC	Cct	lm S - D	Optic
Opaline 82648	W 3000	2940 - On req	00 General
	N 4000	3076 - On req	
	C 6000	3076 - On req	

Electronics

83010	83013	83012	83015
ON/OFF 1 - 3 art. p 150 x l 60 x h 35	ON/OFF 1 - 7 art. p 150 x l 60 x h 35	DALI 1 - 3 art. p 191 x l 63 x h 38	DALI 1 - 6 art. p 220 x l 71 x h 38

Accessories



	description
83020	Brackets

suitable for: MK68_R / MK68_Q


ZeroAir system

Thanks to the experience gained in the design of immersion fixtures, Linea Light group has patented a special system called ZeroAir, which definitively solves the formation of moisture inside the product, so as to preserve the LED circuit from the generation of condensation.



Underwater

MK68_Q | Underwater luminaires | 12 V DC | topLED



694 mm - 11W DC	Cct	lm S - D	Optic
Transp. 82650	W 3000	1470 - On req	36 Diffused
	N 4000	1538 - On req	
	C 6000	1538 - On req	

694 mm - 11W DC	Cct	lm S - D	Optic
Opaline 82654	W 3000	1470 - On req	00 General
	N 4000	1538 - On req	
	C 6000	1538 - On req	

Electronics

83010	83013	83012	83015
ON/OFF 1 - 5 art. p 150 x l 60 x h 35	ON/OFF 1 - 13 art. p 150 x l 60 x h 35	DALI 1 - 5 art. p 191 x l 63 x h 38	DALI 1 - 10 art. p 220 x l 71 x h 38

1290 mm - 20W DC	Cct	lm S - D	Optic
Transp. 82652	W 3000	2205 - On req	36 Diffused
	N 4000	2307 - On req	
	C 6000	2307 - On req	

1290 mm - 20W DC	Cct	lm S - D	Optic
Opaline 82656	W 3000	2940 - On req	00 General
	N 4000	3076 - On req	
	C 6000	3076 - On req	

Electronics

83010	83013	83012	83015
ON/OFF 1 - 3 art. p 150 x l 60 x h 35	ON/OFF 1 - 7 art. p 150 x l 60 x h 35	DALI 1 - 3 art. p 191 x l 63 x h 38	DALI 1 - 6 art. p 220 x l 71 x h 38

MK68 goes down as far as 25 metres

The special structure gives the MK68 capacity to withstand a depth up to 25 metres.

